



Specifications Ledvance LED
Downlight Comfort High Efficiency D
Aluminium White 36W 5200lm 55d -
830 Warm White | 265mm - Cutout
250mm - IP20 - Dimmable, Dali

[View Product](#)

General Information

| | |
|--------------------------|---|
| SKU | 260330 |
| EAN | 4099854687181 |
| Brand | Ledvance |
| Manufacturer Name | DOWNLIGHT COMFORT HIGH EFFICIENCY DALI UGR<19 D250 P 36W 840 U19 WT |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 100000 |

Technical Information

| | |
|-----------------------------|--------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Replaces (Watt) | 2x26 |
| Wattage | 36 |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable with Dali |
| Colour Code | 830 Warm White |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |

| | |
|--------------------------|--------------------------------|
| Light colour options | Single Color |
| Beam Angle (degree) | 55 |
| Luminous Flux (Lumen) | 5200 |
| Luminous Efficacy (lm/W) | 144 |
| Power factor | >0.90 |
| Unified Glare Rating | < 19 - for offices and schools |
| Optical Cover | Opal |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|-------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 250 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Housing | Aluminium |
| Colour of the Fixture | White |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 124 |
| Diameter (mm) | 265 |

Sensor Information

Type of sensor

Why Any-lamp?

No Sensor



Order from the **largest lighting specialist** in Europe



Customised quotation



Up to **7 years warranty**



Easy return process